

PTFE coated fiberglass fabrics

Type	Thickness (mm)	Width (mm)	Length (m)	Adhesive*	Standard Grade	Industrial Grade
FS03	0,070	1000	30		•	
FSAD03	0,070	1000	30	•	•	
FS05	0,120	1000	30		•	
FSAD05	0,120	1000	30	•	•	
FS06	0,135	1000	30		•	
FSAD06	0,135	1000	30	•	•	
FS10	0,230	1000	30		•	
FSAD10	0,230	1000	30	•	•	
FI03	0,068	1000	30			•
FIAD03	0,068	1000	30	•		•
FI05	0,115	1000	30			•
FIAD05	0,115	1000	30	•		•
FI06	0,128	1000	30			•
FIAD06	0,128	1000	30	•		•
FI10	0,215	1000	30			•
FIAD10	0,215	1000	30	•		•

Standard Grade: High wear resistance, mainly used as nonstick and antacid covering

Industrial Grade: Very low superficial roughness and high heat resistance, mainly used for welding machines covering

*Siliconic adhesive

Edition 09.02



fluorseals^{spa}
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it