

Skived Tapes - Virgin p.t.f.e.

Thickness (mm)	Tolerance (mm)	Weight (kg/m ²)	Width (mm)				
			300	600	1000	1200	1500
0,025	+0,01 -0	0,06	•	•			
0,05	+0,01 -0	0,12	•	•			
0,10	+0,01 -0	0,23	•	•	•	•	
0,15	+0,02 -0	0,35	•	•	•	•	
0,20	+0,02 -0	0,46	•	•	•	•	•
0,25	+0,02 -0	0,58	•	•	•	•	•
0,30	+0,02 -0	0,69	•	•	•	•	•
0,35	+0,03 -0	0,81	•	•	•	•	•
0,40	+0,03 -0	0,92	•	•	•	•	•
0,50	+0,03 -0	1,15	•	•	•	•	•
0,60	+0,04 -0	1,38	•	•	•	•	•
0,80	+0,04 -0	1,84	•	•	•	•	•
1	+0,05 -0	2,30	•	•	•	•	•
1,5	+0,10 -0	3,45	•	•	•	•	•
2	+0,20 -0	4,60	•	•	•	•	•
2,5	+0,30 -0	5,75	•	•	•	•	•
3	+0,30 -0	6,90	•	•	•	•	•
4	+0,35 -0	9,20	•	•	•	•	•
5	+0,40 -0	11,50	•	•	•	•	•
6	+0,40 -0	13,80	•	•	•	•	

Tapes can be supplied with one or two etched surfaces in order to enable ptfе to be glued on other materials

•	Additional production
•	Standard production

Tolerance on width: +3%

Weights stated are for guide purposes only

Edition 10.01



fluorseals^{spa}
prodotti in p.t.f.e.